

Nasadki wkrętakowe

Grot do wkrętów z łbem z rowkiem prostym 1/4" DIN 3126 C 6,3

6421 Ciagliwo-twarde, z obszarem skrętnym.

25
mm

642A Ciagliwo-twardy.

642B Ciagliwo-twardy, z obszarem skrętnym.

nr zam.	Szerokość grotu mm	6421 	642A 	642B 	J. op. 	Grubość grotu mm	Długość mm
0003	3,0	–	0,62	–	10	0,5	25
0005	4,0	0,55	–	–	10	0,5	25
0007	4,5	–	0,62	0,82	10	0,6	25
0010	5,5	0,55	0,62	0,82	10	0,8	25
0015	5,5	0,55	–	–	10	1,0	25
0020	6,5	0,55	0,62	0,82	10	1,2	25
0025	8,0	–	0,80	–	10	1,2	25
0030	8,0	–	0,80	0,82	10	1,6	25
		(W546)	(W545)	(W545)			

6421 

642A 

642B 

Grot do wkrętów z łbem z rowkiem prostym 1/4" DIN 3126 C 6,3

Wykonanie: ciagliwo-twarde.

39
mm



nr zam.	Szerokość grotu mm	6423 	J. op. 	Grubość grotu mm	Długość mm
0005	3,0	1,67	10	0,5	39
0010	3,5	1,67	10	0,6	39
0015	4,0	1,67	10	0,8	39
0020	5,5	1,67	10	1,0	39
0025	6,5	1,67	10	1,2	39
0030	8,0	1,67	10	1,2	39
0035	8,0	1,67	10	1,6	39
		(W545)			




Grot do wkrętów z łbem z rowkiem prostym 1/4" DIN 3126 E 6,3

Wykonanie: ciagliwo-twarde.

50
mm



nr zam.	Szerokość grotu mm	6441 	J. op. 	Grubość grotu mm	Długość mm
0005	3,0	2,09	10	0,5	50
0010	3,5	2,09	10	0,6	50
0015	4,0	2,09	10	0,8	50
0025	5,5	2,09	10	0,8	50
0035	6,5	2,09	10	1,2	50
0040	8,0	2,09	10	1,2	50
		(W545)			



Grot do wkrętów z łbem z rowkiem prostym 1/4" DIN 3126 E 6,3

Wykonanie: ciagliwo-twarde.

89
mm

nr zam.	Szerokość grotu mm	6467 	6441 	J. op. 	Grubość grotu mm	Długość mm
0020	4,0	2,38	3,05	10	0,8	89
0030	5,5	2,38	3,05	10	1,0	89
0036	6,5	–	3,05	10	1,2	89
0045	8,0	–	3,05	10	1,2	89
		(W546)	(W545)			

