



CE



											
DS-250-N 1000 Laser & Level	40 3/16" 102 cm	28 3/16x28 3/16" 72x72 cm	2 1/16" 51 mm	7/16" 11 mm	1" 25.4 mm	10" 250 mm	72 1/16x32x45 1/4" 183x80x115 cm	201.7 Lb 91.5 kg	243 Lb 110 kg	1	1
DS-250-N 1300 Laser & Level	51 15/16" 132 cm	36 3/16x36 3/16" 93.5x93.5 cm	2 1/16" 51 mm	7/16" 11 mm	1" 25.4 mm	10" 250 mm	83 7/16x32x45 1/4" 213x80x115 cm	227 Lb 103 kg	276 Lb 125 kg	1	1
DS-250-N 1500 Laser & Level	59 13/16" 152 cm	42 1/16x42 1/16" 107.5x107.5 cm	2 1/16" 51 mm	7/16" 11 mm	1" 25.4 mm	10" 250 mm	9x32x45 1/4" 23x80x115 cm	234 Lb 106 kg	287 Lb 130 kg	1	1

	Ref.	52920	52921	52922	52923	52924	52925
DS-250-N 1000 Laser&Level		230V-50 Hz. RPM 2800	230V-50 UK Hz. 2800	220V-60 Hz. 3400	120V-50 Hz. 2800	120V-60 Hz.inch. 3400	380V-50 Hz. 3F 2800
DS-250-N 1300 Laser&Level	Ref.	52930	52931	52932	52933	52934	52935
		230V-50 Hz. RPM 2800	230V-50 Hz. UK. 2800	220V-60 Hz. 3400	120V-50 Hz. 2800	120V-60 Hz.inch. 3400	380V-50 Hz. 3F 2800
DS-250-N 1500 Laser&Level	Ref.	52940	52941	52942	52943	52944	52945
		230V-50 Hz. RPM 2800	230V-50 Hz.UK 2800	220V-60 Hz. 3400	120V-50 Hz. 2800	120V-60 Hz.Inch. 3400	380V-50 Hz. 3F 2800



2.6 cv/hp

4 CV/HP